

EXTERIOR SUBSTRATES

HARDBOARD

SUPERIOR QUALITY		<u>MPI Approved</u>	<u>Meets MPI GPS</u>	<u>Recommended DFT/Coat</u>	<u>Theoretical Sq. Ft./ Gal./Coat</u>
Primer	05-200 <i>Masterpiece</i> Acry-Prime Int/Ext Primer	6, 39, 137	✓	1.6-2.0	360
Flat Finish	01-100 <i>Masterpiece</i> Int/Ext 100% Acrylic Flat	10		1.7-2.1	360
	- OR - 09-400 <i>Woodtech</i> Solid Color 100% Acrylic Latex Stain	16	✓	1.7-2.0	290
Velvet Finish	01-006 <i>Masterpiece Lifetime</i> Exterior Acrylic Latex Velvet	214	✓	2.5-2.9	250
	- OR - 01-002 <i>Masterpiece</i> Exterior 100% Acrylic Velvet			1.7-2.1	360
Semi-Gloss Finish	01-242 <i>Masterpiece</i> Exterior 100% Acrylic Semi-Gloss	11		1.4-1.7	360
	- OR - 04-402 <i>Industrial</i> Polyurethane Enamel Semi-Gloss	47,94		1.9-2.3	360
Gloss Finish	05-240 <i>Industrial</i> Armor-Guard Exterior 100% Acrylic Gloss			1.4-1.7	360
	- OR - 04-400 <i>Industrial</i> Polyurethane Enamel Gloss	9,48,96		1.8-2.2	360
PREMIUM QUALITY		<u>MPI Approved</u>	<u>Meets MPI GPS</u>	<u>Recommended DFT/Coat</u>	<u>Theoretical Sq. Ft./ Gal./Coat</u>
Primer	05-208-PP <i>Pro Shield</i> Waterborne Primer/Sealer	17,137	✓	1.8-2.2	325
Flat Finish	01-235 <i>Premium Pro Plus</i> Exterior 100% Acrylic Latex Flat	10	✓	1.6-2.0	360
	- OR - 00-047 <i>Premium Pro</i> Quick Dry Alkyd Primer/Finish	49		1.9-2.3	360
Eggshell Finish	01-224 <i>Premium Pro Plus</i> Exterior 100% Acrylic Latex Low Lustre	15	✓	1.5-1.9	360
	- OR - 03-740 <i>Premium Pro</i> Alkyd Int/Ext Eggshell Enamel	51		1.6-2.1	465
Semi-Gloss Finish	03-241 <i>Premium Pro</i> Alkyd Int/Ext Semi-Gloss Enamel	47,94		1.6-2.1	465
Gloss Finish	04-761 <i>Premium Pro</i> Alkyd Int/Ext Gloss Enamel			1.5-1.9	400
STANDARD QUALITY		<u>MPI Approved</u>	<u>Meets MPI GPS</u>	<u>Recommended DFT/Coat</u>	<u>Theoretical Sq. Ft./ Gal./Coat</u>
Primer	01-727 <i>Premium Pro</i> Exterior 100% Acrylic Latex Primer	6	✓	1.3-1.7	400
Flat Finish	01-204 <i>Professional</i> Pro Choice Exterior 100% Acrylic Flat- Cold Temp			1.5-1.8	300
Velvet Finish	01-207 <i>Professional</i> Pro Choice Exterior 100% Acrylic Velvet- Cold Temp			1.5-1.8	300
SPECIAL PURPOSE		<u>MPI Approved</u>	<u>Meets MPI GPS</u>	<u>Recommended DFT/Coat</u>	<u>Theoretical Sq. Ft./ Gal./Coat</u>
Flat Finish	05-338 <i>Hi-Performance</i> Polar-Kote Flat (for low temp application)			1.5-1.9	360
Satin Finish	05-337 <i>Hi-Performance</i> Polar-Kote Satin (for low temp application)			1.4-1.8	360
Semi-Gloss Finish	05-502 <i>Industrial</i> Acrylic DTM Polyurethane Enamel	11		1.6-2.0	320

✓ = Listed Product Meets MPI Green Performance™ Standard

For product limitations, please refer to the product's Technical Data Sheet. Contact your Columbia Paint Representative for more details.