



EXTERIOR SUBSTRATES

VINYL SIDING

SUPERIOR QUALITY		<u>MPI Approved</u>	<u>Meets MPI GPS</u>	<u>Recommended DFT/Coat</u>	<u>Theoretical Sq. Ft./Gal./Coat</u>
Primer	05-200 <i>Masterpiece</i> Acry-Prime Int/Ext Primer	6, 39, 137	✓	1.6-2.0	360
Flat Finish	01-100 <i>Masterpiece</i> Int/Ext 100% Acrylic Flat	10		1.7-2.1	360
Velvet Finish	01-006 <i>Masterpiece Lifetime</i> Exterior Acrylic Latex Velvet - OR -	214	✓	2.5-2.9	250
	01-002 <i>Masterpiece</i> Exterior 100% Acrylic Velvet			1.7-2.1	360
Semi-Gloss Finish	01-242 <i>Masterpiece</i> Exterior 100% Acrylic Semi-Gloss	11		1.4-1.7	360
Gloss Finish	05-240 <i>Industrial Armor-Guard</i> Exterior 100% Acrylic			1.4-1.7	360
PREMIUM QUALITY		<u>MPI Approved</u>	<u>Meets MPI GPS</u>	<u>Recommended DFT/Coat</u>	<u>Theoretical Sq. Ft./Gal./Coat</u>
Primer	05-208 <i>Pro Shield</i> Waterborne Primer/Sealer	17,137	✓	1.8-2.2	325
Flat Finish	01-235 <i>Premium Pro Plus</i> Exterior 100% Acrylic Latex Flat	10	✓	1.6-2.0	360
Eggshell Finish	01-224 <i>Premium Pro Plus</i> Exterior 100% Acrylic Latex Low Lustre	15	✓	1.5-1.9	360
STANDARD QUALITY		<u>MPI Approved</u>	<u>Meets MPI GPS</u>	<u>Recommended DFT/Coat</u>	<u>Theoretical Sq. Ft./Gal./Coat</u>
Primer	01-727 <i>Premium Pro</i> Exterior 100% Acrylic Latex Primer	6	✓	1.3-1.7	400
Flat Finish	01-204 <i>Professional</i> Pro Choice Exterior 100% Acrylic Flat- Cold Temp			1.5-1.8	300
Velvet Finish	01-207 <i>Professional</i> Pro Choice Exterior 100% Acrylic Velvet- Cold Temp			1.5-1.8	300
SPECIAL PURPOSE		<u>MPI Approved</u>	<u>Meets MPI GPS</u>	<u>Recommended DFT/Coat</u>	<u>Theoretical Sq. Ft./Gal./Coat</u>
Flat Finish	05-338 <i>Hi-Performance</i> Polar-Kote Flat (for low temp application)			1.5-1.9	360
Satin Finish	05-337 <i>Hi-Performance</i> Polar-Kote Satin (for low temp application)			1.4-1.8	360

NOTE: Do not paint any darker than the original color of the siding, or the siding can get too hot from sunshine and warp permanently.

✓ = Listed Product Meets MPI Green Performance™ Standard

For product limitations, please refer to the product's Technical Data Sheet. Contact your Columbia Paint Representative for more details.